

TURCK 7/8" minifast® Connectivity Products



5 and 6-Wire Receptacles, Front Mount, 1/2-14 NPT Threads

- NEMA 1, 3, 4, 6P
- IEC IP67 Protection



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>RKF ..NPT</p> <p>Typical panel cutout 22.5 mm</p>	RKF 50-*M/NPT	RSF 50-*M/NPT	5x18 AWG, 105°C, 9 A, standard duty	<p>Female</p> <ol style="list-style-type: none"> BK BU GN/YE BN WH
	RKF 511-*M/NPT	RSF 511-*M/NPT	5x18 AWG, 105°C, 9A, automotive color code	<ol style="list-style-type: none"> RD/WH RD/BU GN RD/OG RD/BK
	RKF 55-*M/NPT	RSF 55-*M/NPT	5x16 AWG, 105°C, 10 A, automotive color code	<ol style="list-style-type: none"> WH RD GN RD/OG RD/BK
	RKF 56-*M/NPT	RSF 56-*M/NPT	5x16 AWG, 105°C, 10 A, heavy duty	<ol style="list-style-type: none"> WH RD GN OG BK
	RKF 58-*M/NPT	RSF 58-*M/NPT	5x18 AWG, 105°C, 300 V, 9 A, heavy duty	<ol style="list-style-type: none"> WH RD GN OG BK
<p>RSF ..NPT</p> <p>Typical panel cutout is 22.5 mm</p>	RKF 61-*M/NPT	RSF 61-*M/NPT	6x18 AWG, 105°C, 9 A, standard duty	<p>Female</p> <ol style="list-style-type: none"> GN WH BU GY YE BN
	RKF 66-*M/NPT	RSF 66-*M/NPT	6x16 AWG, 105°C, 10 A, heavy duty	<p>Male</p> <ol style="list-style-type: none"> WH RD GN OG BK BU
	RKF 68-*M/NPT	RSF 68-*M/NPT	6x18 AWG, 105°C, 600 V, 9 A, heavy duty	<p>Male</p> <ol style="list-style-type: none"> WH RD GN OG BK BU

Receptacles

Standard lead length is 0.3 Meters. Consult factory for other lengths.
 ** Standard housing material is nickel plated brass.. "RSF .."; "RSFV .." indicates stainless steel housing.
 For locknuts to be included, add "W/LN" to the end of the part number.
 To specify PVC jacketed cable, add "/S717" to the end of the part number.