

Conduit Adapters, 2 Port

- Attaches to Standard Crouse-Hinds 3/4" Form 8, Mark 9 Conduit Bodies for Transition to 3-5 Wire *minifast* Connectors
- Gasket and 8-32 x 1/2 Mounting Screws
- IP67 Protection (only when all receptacles are mated or covered with plugs)
- Terminal Strips Accept Up to 12 AWG Wires



Housing Style	Part Number	Features	Pinout	Wiring Diagram
	CA-2/RKF 30	Nylon housing, 80°C, 250 V, 9A, attaches to standard conduit body for transition to 3-wire <i>minifast</i> connector	Female 	
	CA-2/RKF 30/S651	Nylon housing, 80°C, 250 V, 9A, attaches to standard conduit body for transition to 3-wire <i>minifast</i> connector, parallel wired	Male 	
	CA-2/RKF 40	Nylon housing, 80°C, 250 V, 9A, attaches to standard conduit body for transition to 4-wire <i>minifast</i> connector	Female 	
	CA-2/RKF 40/S651	Nylon housing, 80°C, 250 V, 9A, attaches to standard conduit body for transition to 4-wire <i>minifast</i> connector, parallel wired	Male 	
	CA-2/RKF 50	Nylon housing, 80°C, 250 V, 9A, attaches to standard conduit body for transition to 5-wire <i>minifast</i> connector	Female 	
	CA-2/RKF 50/S651	Nylon housing, 80°C, 250 V, 9A, attaches to standard conduit body for transition to 5-wire <i>minifast</i> connector, parallel wired	Male 	

Standard receptacle housing material is nickel plated brass.. "RKF"; "RKFV" indicates stainless steel.
 Example: CA-2/RKFV 50.