



14-Pin Cordsets

- For *eurofast*®/*picofast*® Junction Boxes and multi-conductor applications
- IEC IP67 Protection



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>BKM ..</p>	<p>BKM 14-836-* BKWM 14-836-*</p>	<p>BSM 14-836-* BSWM 14-836-*</p>	<p>PVC Black, 10x24 AWG, 105°C, 30 VAC/VDC, 3 A, 6.6 mm OD, Cable #RF50836-*M†, 10-wire DC applications, junction box, VB 803M(Z)-BS14, <i>flexlife</i>®</p>	<p>Female</p> <p>Male</p>
<p>BKWM ..</p>	<p>BKM 14-954-*/S101 BKWM 14-954-*/S101</p>	<p>BSM 14-954-*/S101 BSWM 14-954-*/S101</p>	<p>TPE Black, 10x24 AWG, 105°C, 30 VAC/VDC, 3 A, 7.0 mm OD, Cable #RF50954-*M†, 10-wire DC applications, junction box, VB 803M(Z)-BS14, <i>flexlife</i>-20, high flex - over 20 million cycles</p>	
<p>BSM ..</p>				
<p>BSWM ..</p>	<p>BKM 14-917-* BKWM 14-917-*</p>	<p>BSM 14-917-* BSWM 14-917-*</p>	<p>PVC Yellow, 12x24 AWG, 105°C, 30 VAC/VDC, 3 A, 7.0 mm OD, Cable #RF50917-*M†, 12-wire DC applications, junction boxes 4MBM12-5-BS14 & VB 404M(Z)-BS14, <i>flexlife</i></p>	

Cordsets

* Length in meters. Standard cable lengths are 5 and 10 meters. Consult factory for other lengths. Standard coupling nut material is nickel plated brass.. "BKM.."; "BKMK.." indicates nylon and "BKMV.." indicates stainless steel.
 † See Section N for *reelfast*® cable information.