

12-Pin Cordsets, AC & DC Color Code

- For *eurofast*®, *minifast*®, and *microfast*® Junction Boxes and multi-conductor Applications
- IEC IP67 Protection
- 300 V, 6 A



Connector Style	Female Part Number	Male Part Number	Features	Pinout
<p>CK*M..</p>	CKBM 12-7-* CKBWM 12-7-*	CSBM 12-7-* CSBWM 12-7-*	PVC Black, 7x18 AWG 105°C, 7.2 mm OD, Cable #RF50715-*M†, 4-port, AC Color Code, Standard Wiring with LEDs, <i>flexlife</i> ®	<ol style="list-style-type: none"> 1. WH/BK 2. BK 3. WH 4. RD 5. OG 6. BU 7. GN
<p>CK*WM..</p>	CKBM 12-11-* CKBWM 12-11-*	CSBM 12-11-* CSBWM 12-11-*	PVC Black, 11x18 AWG, 105°C, 10 mm OD, Cable #RF50716-*M†, 8-port, AC Color Code, Standard Wiring with LEDs, <i>flexlife</i>	<ol style="list-style-type: none"> 1. OG 2. BU 3. WH/BK 4. RD/BK 5. GN/BK 6. OG/BK 7. BU/BK 9. GN 10. RD 11. WH 12. BK <p>Female</p>
<p>CS*M..</p>	CKCM 12-7-* CKCWM 12-7-*	CSCM 12-7-* CSCWM 12-7-*	ITC/PLTC PVC Yellow, 7x18 AWG, 105°C, 8.4 mm OD, Cable #RF50637-*M†, 4-port 1 signal per port, DC Color Code, <i>flexlife</i>	<ol style="list-style-type: none"> 1. WH 2. GN 3. YE 4. GY 10. BU 11. BN 12. GN/YE
<p>CS*WM..</p>	CKCM 12-7-*/S90 CKCWM 12-7-*/S90	CSCM 12-7-*/S90 CSCWM 12-7-*/S90	TPU Yellow, 7x18 AWG, 90°C, 7.2 mm OD, Cable #RF50676-*M†, 4-port 1 signal per port, DC Color Code, Cut/Abrasion Immune	<ol style="list-style-type: none"> 1. WH 2. GN 3. YE 4. GY 10. BU 11. BN 12. GN/YE <p>Male</p>
<p>CK*WM..</p>	CKCM 12-11-* CKCWM 12-11-*	CSCM 12-11-* CSCWM 12-11-*	ITC/PLTC PVC Yellow, 11x18 AWG, 105°C, 10.5 mm OD, Cable #RF51088-*M†, 8-port 1 Signal per port, DC Color Code, <i>flexlife</i>	<ol style="list-style-type: none"> 1. WH 2. GN 3. YE 4. GY 5. PK 6. RD 7. BK 8. VT 10. BU 11. BN 12. GN/YE
<p>CS*WM..</p>	CKCM 12-11-*/S90 CKCWM 12-11-*/S90	CSCM 12-11-*/S90 CSCWM 12-11-*/S90	TPU Yellow, 11x18 AWG, 90°C, 10 mm OD, Cable #RF50678-*M†, 8-port 1 signal per port, DC Color Code, Cut/Abrasion Immune	<ol style="list-style-type: none"> 1. WH 2. GN 3. YE 4. GY 5. PK 6. RD 7. BK 8. VT 10. BU 11. BN 12. GN/YE

* Length in meters.

Standard cable lengths are 5 and 10 meters. Consult factory for other lengths.

Standard coupling nut material is nickel plated brass.. "CKB(C)M.."; "CKB(C)MV.." indicates stainless steel coupling nut.

† See Section N for *reelfast*® cable information.

** Color Code:

C = DC color code

B = AC color code, standard wiring with LEDs