





## 12-Pin Receptacles, Front Mount

- For use with Junction Box Home Run Cables
- IEC IP67 Protection
- 300 V, 6 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p><b>CS(K)F</b></p> <p>Typical panel cutout is 20.4 x 19 x 20.4 mm</p>	CKF 12-7-*	CSF 12-7-*	Nickel plated brass, 7x18 AWG, 105° C, 4-port, 1 signal per port	<ol style="list-style-type: none"> <li>BN</li> <li>BU</li> <li>WH</li> <li>GN</li> <li>YE</li> <li>GY</li> <li>GN/YE</li> </ol>
	CKF 12-9-*	CSF 12-9-*	Nickel plated brass, 9x18 AWG, 105° C, 6-port, 1 signal per port	<ol style="list-style-type: none"> <li>BN</li> <li>BU</li> <li>WH</li> <li>GN</li> <li>YE</li> <li>GY</li> <li>PK</li> <li>RD</li> <li>GN/YE</li> </ol>
	CKF 12-11-*	CSF 12-11-*	Nickel plated brass, 11x18 AWG, 105° C, 8-port, 1 signal per port	<ol style="list-style-type: none"> <li>BN</li> <li>BU</li> <li>WH</li> <li>GN</li> <li>YE</li> <li>GY</li> <li>PK</li> <li>RD</li> <li>BK</li> <li>VT</li> <li>GN/YE</li> </ol>
	CKF 12-12-*	CSF 12-12-*	Nickel plated brass, 12x18 AWG, 105° C, 8-port, 1 signal per port	<ol style="list-style-type: none"> <li>BN</li> <li>OG</li> <li>BU</li> <li>WH</li> <li>GN</li> <li>YE</li> <li>GY</li> <li>PK</li> <li>RD</li> <li>BK</li> <li>VT</li> <li>GN/YE</li> </ol>
	CKF 12-12-*/S817	CSF 12-12-*/S817	Nickel plated brass, 12x18 AWG, 105° C, 8-port, 1 signal per port	<ol style="list-style-type: none"> <li>BN</li> <li>BU</li> <li>WH</li> <li>GN/YE</li> <li>OG</li> <li>YE</li> <li>GY</li> <li>PK</li> <li>RD</li> <li>BN/WH</li> <li>BU/WH</li> <li>GN/WH</li> </ol>



Cordsets

\* Length in meters. Standard lead length is 1 meter. Consult factory for other lengths.  
 "CSFL .." indicates long mounting threads; "CSFLV .." indicates stainless steel housing with long threads.  
 To specify PVC jacketed cable, add "/S717" to the end of the part number.