

19-Pin Receptacles, Front Mount

- For use with Junction Box Home Run Cables
- IEC IP67 Protection
- 150 V, 9 A (pins 6, 12, 19), all others 2 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>CS(K)F</p> <p>Typical panel cutout is 20.4 x 19 x 20.4 mm</p>	CKF 19-11-*	CSF 19-11-*	Nickel plated brass, 3x18, 8x22 AWG, 105°C, 4-port, 2 signals per port	<ol style="list-style-type: none"> GY RD/BU GN BU GY/PK WH/GN GN/YE BN/GN WH YE BN <p>Female</p>
<p>CS(K)F</p> <p>Typical panel cutout is 20.4 x 19 x 20.4 mm</p>	CKF 19-15-*	CSF 19-15-*	Nickel plated brass,, 3x18, 12x22 AWG, 105°C, 6-port, 2 signals per port	<ol style="list-style-type: none"> RD GY RD/BU GN BU GY/PK WH/GN WH/YE GN/YE YE/BN BN/GN WH YE PK BN
<p>CS(K)FL</p> <p>Typical panel cutout is 20.4 x 19 x 20.4 mm</p>	CKF 19-19-*	CSF 19-19-*	Nickel plated brass, 3x18, 16x22 AWG, 105°C, 8-port, 2 signals per port	<ol style="list-style-type: none"> VT RD GY RD/BU GN BU GY/PK WH/GN WH/YE WH/GY BK GN/YE YE/BN BN/GN WH YE PK GY/BN BN <p>Male</p>

* Length in meters. Standard lead length is 1 meter. Consult factory for other lengths.
 "CSFL .." indicates long mounting threads; "CSFLV .." indicates stainless steel housing with long threads.
 To specify PVC jacketed cable, add "/S717" to the end of the part number.