


12-Pin Receptacles, Front Mount

- For use with Junction Box Home Run Cables
- IEC IP67 Protection
- 300 V, 6 A



Housing Style	Female Part Number	Male Part Number	Features	Pinout
<p>CS(C)(NF)</p> <p>Typical panel cutout is 20.4 x 19 x 20.4 mm</p>	CKCF 12-7-*	CSCF 12-7-*	Nickel plated brass, 7x18 AWG, 105°C, 4-port, 1 signal per port, 4MB12Z-4-*	<ol style="list-style-type: none"> 1. WH 2. GN 3. YE 4. GY 10. BU 11. BN 12. GN/YE <p>Female</p>
<p>CS(C)(NF)</p> <p>Typical panel cutout is 20.4 x 19 x 20.4 mm.</p>	CKCF 12-11-*	CSCF 12-11-*	Nickel plated brass, 11x18 AWG, 105°C, 8-port, 1 signal per port, 8MB12Z-4-*	<ol style="list-style-type: none"> 1. WH 2. GN 3. YE 4. GY 5. PK 6. RD 7. BK 8. VT 10. BU 11. BN 12. GN/YE <p>Female</p>
<p>CS(C)(N)FL</p> <p>Typical panel cutout is 20.4 x 19 x 20.4 mm.</p>	CKNF 12-9-*	CSNF 12-9-*	Nickel plated brass, 9x18 AWG, 105°C, 4-port, 1 isolated circuit per port or 2 circuits per port with common positive	<ol style="list-style-type: none"> 1. BN 2. WH 3. BK 4. GN 5. RD 6. OG 7. BU 8. YE 9. VT <p>Male</p>

* Length in meters. Standard lead length is 1 meter. Consult factory for other lengths.

"CSC(N or R)FL .." indicates long mounting threads; "CSC(N or R)FLV .." indicates stainless steel housing with long threads.

To specify PVC jacketed cable, add "/S717" to the end of the part number.