

**minifast® Drop Cordsets, 2-Wire Analog or HART Control Circuits**

- Straight Male Connectors
- IEC IP 67 Protection
- 300 V, 9 A  
(use as ITC limited to 150 V, 5 A)



FM tested to the cable sealing requirements of NEC Article 501-5(E)(2)

Housing Style	Part Number	Cable	Application	Pinout
<p><b>P-RSM..</b></p>	P-RSM 40-330-*M	ITC-Exposed Run/Direct Burial/PLTC PVC Plum 3x18 AWG, 1 STP with GND Foil/Drain (20) 105°C 7.2 mm OD Cable #RF51162-*M†	<i>Intrinsically Safe Analog or HART control circuits in Class I, Division 1 hazardous locations.</i>	1. BU 2. BN 3. Drain 4. GN/YE
	P-RSM 40-950-*M	ITC/PLTC PVC Blue 3x18 AWG 1 STP with GND Foil/Drain (20) 105°C 7.2 mm OD Cable #RF50950-*M†		
	P-RSM 45-327-*M	ITC/PLTC PVC Blue 3x16 AWG, 1 STP with GND Foil/Drain (18) 105°C 7.6 mm OD Cable #RF51327-*M†	<i>Analog or HART control circuits in Class I, Division 2 hazardous locations** or unclassified locations.</i>	
	P-RSM 46-124-*M	ITC/PLTC PVC Plum 3x18 AWG, 1 STP with GND Foil/Drain (20) 105°C 7.2 mm OD Cable #RF51124-*M†		
	P-RSM 461-124-*M			
<p><b>P-RSM..</b></p>	P-RSM 40A-947-*M	ITC/PLTC Armor Plum 3x18 AWG, 1 STP with GND Foil/Drain (20) 105°C 13.5 mm OD Cable #RF50947-*M†	<i>Analog or HART control circuits in Class I, Division 2 hazardous locations** or unclassified locations.</i>	1. BU 2. BN 3. Drain 4. GN/YE

minifast cordsets

\* Length in meters. Standard cable lengths are 2, 4, 5, 6, 8 and 10 meters. Consult factory for other lengths.  
Standard coupling nut material is nickel plated brass "P-RSM.."; "P-RSV.." indicates 316 stainless steel.

† See Section F for **reelfast®** cable information.

\*\* Use with **lokfast minifast** guards (Part Number: LOCK-MINI) in Class I, Division 2 applications.

Note: See **TURCK** Control Drawing QCF-00147 ([www.turck.com/fmcd](http://www.turck.com/fmcd)) for guidance on installation in hazardous locations.