

7, 8, and 9-Wire minifast[®] extremelife[®] Control Cordsets

- Straight Female Connectors
- NEMA 1, 3, 4, 6P and IEC IP 67 Protection



Housing	Part Number	Cable	Features	Pinout
	P-RKV 70-182-*M	PVC Black 5x18 AWG, 2 STP with GND 90°C 300 V, 9 A 10.4 mm OD Cable #RF51182-*M [†]	<i>extremelife-25</i> UL 1309 approved 2-wire Analog x 2	<ol style="list-style-type: none"> 1. BU 2. BN 3. Drain 4. WH 5. BK 6. Drain 7. GN/YE
	P-RKV 80-073-*M	PVC Blue, Braided Armor 8x18 AWG, 4 STP 90°C 300 V, 9 A 17.8 mm OD Cable #RF51073-*M [†]	<i>extremelife-25</i> Braided Armor Cable UL 1309 approved 2-wire Analog x 4	<ol style="list-style-type: none"> 1. BK 2. WH 3. BU 4. RD 5. YE 6. BN 7. GY 8. GN
	P-RKV 80-158-*M	TPE Black 8x18 AWG, 4 STP 90°C 300 V, 9 A 15.1 mm OD Cable #RF51158-*M [†]	<i>extremelife-55</i> UL 1309 approved 2-wire Analog x 4	<ol style="list-style-type: none"> 1. BK 2. WH 3. BU 4. RD 5. YE 6. BN 7. GY 8. GN
	P-RKV 100-183-*M	PVC Black 9x18 AWG, 4 STP with GND 90°C 300 V, 7 A 13.2 mm OD Cable #RF51183-*M [†]	<i>extremelife-25</i> UL 1309 approved 2-wire Analog x 4	<ol style="list-style-type: none"> 1. WH/BK 2. BK/WH 3. WH/GN 4. GN/WH 5. WH/RD 6. RD/WH 7. N/C 8. GN/YE 9. WH/OG 10. OG/WH
	P-RKV 100-189-*M	TPE Black 9x18 AWG, 4 STP with GND 90°C 300 V, 7 A 15.1 mm OD Cable #RF51189-*M [†]	<i>extremelife-55</i> UL 1309 approved 2-wire Analog x 4	<ol style="list-style-type: none"> 1. WH/BK 2. BK/WH 3. WH/GN 4. GN/WH 5. WH/RD 6. RD/WH 7. N/C 8. GN/YE 9. WH/OG 10. OG/WH

* Length in meters. Standard cable lengths are 2, 4, 6, 8 and 10 meters. Consult factory for other lengths.

Standard coupling nut material is 316 stainless steel "P-RKV .."; "P-RKM .." indicates nickel plated brass.

[†] See pages K236 - K244 for *reelfast*[®] cable information.