


PVC-Coated Conduit Bodies and Fittings



8" Movement
Coupling shown uncoated



Coupling shown uncoated

Innovative Design Makes Installations Easier.

- No disassembly necessary to install
- Fast, simple and requires fewer steps
- True internal bonding jumper — no external grounding strap required
- Tamper-proof internal jumper protected from the environment
- Exceeds code requirements for long conduit runs to permit linear movement

No disassembly required.

Ocal® PVC-Coated XJG Rigid Conduit Expansion Coupling

When you install a rigid expansion coupling in a long conduit run, you normally need three hands, two strong backs and lots of patience. Now you can relax.

With the no-hassle XJG Rigid Conduit Expansion Coupling, installation's just a few turns and you're done.

The XJG Rigid Conduit Expansion Coupling features innovations that provide convenience to the installer, saving time and money on the job. No disassembly is needed during installation, requiring fewer tools and less opportunity for lost pieces. It also features a true internal bonding jumper, eliminating the need for external jumpers, so there are fewer parts to buy and install.

If you need a fitting that can give and take without a lot of hassle, reach for the XJG Rigid Conduit Expansion Coupling. It's the latest breakthrough in the industry's leading line of conduit fittings.



1

Slide the fitting onto the conduit until it stops at the internal sliding bushing. Tighten and you're ready. No parts to reassemble!



2


With a wrench, tighten the gland nut to create a raintight seal around the conduit.



3

Thread the next length of conduit into the other end of the fitting and tighten. You're done!

PVC-Coated Conduit Bodies and Fittings



Coupling shown uncoated

PVC-Coated XJG Rigid Conduit Expansion Couplings

CAT. NO.	PIPE SIZE IN. METRIC SIZE DESIGNATOR*	MOVEMENT IN. MM	A DIAMETER IN. MM	B LENGTH IN. MM	C HEIGHT IN. MM
XJG24- 21	¾ 21	4.00 101.60	2.43 61.72	10.00 254.00	2.75 69.85
XJG28- 21	¾ 21	8.00 203.20	2.43 61.72	14.00 355.60	2.75 69.85
XJG34- 27	1 27	4.00 101.60	2.67 67.82	10.00 254.00	2.99 75.95
XJG38- 27	1 27	8.00 203.20	2.67 67.82	14.00 355.60	2.99 75.95
XJG44- 35	1¼ 35	4.00 101.60	3.36 85.34	10.56 268.22	3.68 93.47
XJG48- 35	1¼ 35	8.00 203.20	3.36 85.34	14.56 369.82	3.68 93.47
XJG54- 41	1½ 41	4.00 101.60	3.36 85.34	10.56 268.22	3.68 93.47
XJG58- 41	1½ 41	8.00 203.20	3.36 85.34	14.56 369.82	3.68 93.47
XJG64- 53	2 53	4.00 101.60	3.86 98.04	11.25 285.75	4.18 106.17
XJG68- 53	2 53	8.00 203.20	3.86 98.04	15.25 387.35	4.18 106.17
XJG74- 63	2½ 63	4.00 101.60	4.96 125.98	12.12 307.85	5.25 133.35
XJG78- 63	2½ 63	8.00 203.20	4.96 125.98	16.12 409.45	5.25 133.35
XJG84- 78	3 78	4.00 101.60	4.96 125.98	12.12 307.85	5.25 133.35
XJG88- 78	3 78	8.00 203.20	4.96 125.98	16.12 409.45	5.25 133.35
XJG94- 91	3½ 91	4.00 101.60	6.37 161.80	12.87 326.90	6.75 171.45
XJG98- 91	3½ 91	8.00 203.20	6.37 161.80	16.87 428.50	6.75 171.45
XJG104- 103	4 103	4.00 101.60	6.37 161.80	12.87 326.90	6.75 171.45
XJG108- 103	4 103	8.00 203.20	6.37 161.80	16.87 428.50	6.75 171.45
XJG1208- 129	5 129	8.00 203.20	7.99 161.80	18.87 479.30	8.56 217.42




* Metric size designator (ANSI C80.1 - 1994).
Dimensions shown are for uncoated coupling.



XJG24-G
4" Movement

Standard Materials/Finish

- Body/Finish: Ductile iron with nominal 40-mil PVC exterior coating
- Internal Bonding Jumper: Tinned copper braid

CAT. NO.	COLOR
XJG24- _	
_	= space for color identifier
G	= Gray 
W	= White 
B	= Blue 
Custom colors also available.	